




STAINLESS STEEL SEWAGE PUMPS

- Liquid temperature : 0~40°C / 32~104°F
- HP range : 0.5~0.75HP / 0.4~5.5KW
- PH : 5~9
- Rated Speed : 2900 / 3450 rpm
- Protection calss : IP68
- Maximum depth : 8M

Features

- 1 · Non-clogging vortex impeller.
- 2 · Suspended impeller and high efficacy flow channel design, no blocking. The pass solid is 50mm.
- 3 · The material is stainless steel which can endure light acid and alkali.






Applications

- 1 · Industrial sewage discharge
- 2 · Sewage and wastewater discharge containing chemicals

Specification

Model No.	Output		Outlet	Pass Solid	LPM Flow @ Head						Max Head(M)	Dimension		Weight
	HP	KW	mm inch	Dia(mm)	Max Flow(LPM)	3M	6M	9M	12M	15M		L x W x H(mm)	L x W x H(mm)	
SB-05	1/2	0.4	50 2"	30	320	290	180	50	-	-	10	223 x 132 x 395	14	14
SB-10	1	0.75	50 2"	30	410	370	250	100	-	-	11	223 x 132 x 425	21	21
SB-20	2	1.5	80 3"	35	630	590	490	380	240	55	16	390 x 210 x 530	32	32
Model No.	Output		Outlet	Pass Solid	LPM Flow @ Head						Max Head(M)	Dimension		Weight
	HP	KW	mm inch	Dia(mm)	Max Flow(LPM)	3M	5M	10M	15M	20M		L x W x H(mm)	L x W x H(mm)	
SB-30	3	2.2	80 3"	35	800	750	670	440	180	-	18	390 x 210 x 550	34	34
SB-50	5	3.7	100 4"	45	1100	1000	880	590	290	-	20	525 x 250 x 635	45	45
SB-75	7.5	5.5	100 4"	50	1200	1150	1050	800	520	190	23	525 x 250 x 675	54	54

Sectional View



Standard Accessories

Model No.	Accessories	
SB-05	Flange, Hose connection	
SB-10	Flange, Hose connection	
SB-20	Flange, Hose connection	
SB-30	Elbow, Flange	
SB-50	Elbow, Flange	
SB-75	Elbow, Flange	



Dimension

Dimension													
Model	L	L1	L2	W	W1	H	H1	H2	H3	H4	PCD	G	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	inch
SB-05	215	-	75	155	112	445	386	105	105	130	83	2	
SB-10	260	-	100	165	140	415	340	120	120	148	117	3	
SB-20	380	250	100	210	145	560	485	122	135	160	117	3	
SB-30	380	250	100	210	145	580	505	122	135	160	117	3	
SB-50	470	285	183	216	183	620	525	155	210	240	155	4	
SB-75	470	285	183	216	183	640	555	155	210	240	155	4	

